



Nikon D610 Outer Case Replacement

This guide will show you how to properly remove the outside case of the Nikon D610.

Written By: Daniel Eagan



INTRODUCTION

This guide will help you to get to the internal components of the camera.

TOOLS:

- [Spudger](#) (1)
 - [Desoldering Braid](#) (1)
 - [Soldering Station](#) (1)
 - [Phillips #00 Screwdriver](#) (1)
-

Step 1 — Battery



- First, power off the device.

Step 2



- Set the camera so that it is sitting on its side.
- Open the battery compartment door by sliding the release button towards the lens.
- This will cause the door to "pop" open slightly

Step 3



- Now lift open the battery compartment door.
- Push the yellow tab lock towards the center to release the battery.
- ⓘ This will cause the battery to jump up as there is a spring at the bottom.
- Pull straight out, slowly on the battery.
- ⚠ Make sure you pay attention to which way the battery goes .

Step 4 — Outer Case



- After removal of the battery. Pull the battery compartment door away from the lens.
- There are eleven Philips head screws that hold the bottom cover on, including a few inside the battery compartment.
- Remove all the screws and the bottom face should pop off easily.

Step 5



- Then next step is removing the seven Philips #00 screws that hold the rear face plate on.
- There are screws hidden in three separate spots.
- One is under the rubber doors on the left side of the camera. the next one at the eye hole.
- The final one involves taking off the small dial that is about half an inch to the right of the eye hole.
- Removing this dial involves putting a spungder tool behind it and applying a gradual amount of pressure.

Step 6




- The rear face plate will include the LCD display it separates from the body of the camera with a small tug.
- ⚠ Do not pull too hard otherwise you risk breaking the ribbon wire that connects the controls and the screen.
- Once there is enough space it will be possible to gently pull the ribbon cable out of their ports.



Step 7



- The next piece to come off is the front plate and the red grip.
 - The front plate is held on by 2 Philips #00 screws on the front and two more beneath the flash bulb.
 - Remove the two Phillips #00 screws holding on the grip and it slides off easily.
- i** After removing the screws the face plate comes off by pulling it straight off to avoid damage.

Step 8



- It is now possible to remove the last three Philips #00 screws that are hidden under the memory card slot door.
 - The screws come out and the cover comes straight off.
 - The last cover plate is the top. The top is held on by two screws located just beneath the rim of the cover.
-  The top should be pulled off very slowly. There are several electronic components that connect between the body and the top.
-  There are three wires that need to be disconnected.

To reassemble your device, follow these instructions in reverse order.

This document was last generated on 2017-06-25 11:50:02 AM.